CEN/TS 17693-1:2021 (E)

Contents		Page
Euro	pean foreword	3
Intro	oduction	3
1	Scope	5
2	Normative references	
3 3.1 3.2	Terms, definitions, abbreviations and symbols Terms Abbreviations and symbols	5 6
4	Principle of the test	
5 5.1 5.2	Reagents Lime Water	7 7
6	Apparatus	
7 7.1 7.2 7.3	Preparation of the test portions If D_{\max} is greater than 50 mm If D_{\max} is ranging between 5 mm and 50 mm If D_{\max} is smaller than or equal at 5 mm	8 8 9
8	Test procedure	9
8.1	Water calibration of the pH-meter	
8.2 8.3	Main test procedureAlternative test procedure	10 10
9 9.1 9.2 9.3	Expression of results and determination of the LFP (LMO) of the soilpH vs added lime graph	11 11 11
9.4	Abnormal or out of range pH results	
10	Test report	
Anne	ex A (informative) Example of a test data sheet	13
Bibli	ography	16

European foreword

This document (CEN/TS 17693-1:2021) has been prepared by Technical Committee CEN/TC 396 "Earthworks", the secretariat of which is held by AFNOR.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national standards body. A complete listing of these bodies can be found on the CEN website.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

UNI CEN/TS 17693-1:2022

Introduction

This document describes the reference method for the determination of the lime fixation point (LFP) of soils, also called lime modification optimum (LMO).

LFP (LMO) is the theoretical lime content from which can occur the setting and hardening of soil-lime mix, resulting from the pozzolanic reactions due to the combination of lime with clay components of the soil.

It can be considered as the optimal lime amount to be added in a soil in order to perform its improvement, and the minimal lime amount from which stabilization can occur (terms "improvement" and "stabilization" as defined in EN 16907-4).

4

1 Scope

This document describes the reference method for the determination of the lime fixation point (LFP) in soil treatment for earthworks.

The test consists in measuring the lowest quantity of lime to be added in a soil suspension in water that will result in a pH value of the soil-lime mix suspension of 12,4, measured at 25 °C \pm 1 °C.

This test method cannot be used to provide information about soil reactivity with lime, or other performance values (mechanical characteristics of soil-lime mixes) applicable for improvement or stabilization purposes. Those performance tests will be conducted in a laboratory from a specific study, the lime dosage to be applied being indicated from this method.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 459-1, Building lime - Part 1: Definitions, specifications and conformity criteria

ISO 3310-1, Test sieves - Technical requirements and testing - Part 1: Test sieves of metal wire cloth

ISO 3310-2, Test sieves - Technical requirements and testing - Part 2: Test sieves of perforated metal plate

3 Terms, definitions, abbreviations and symbols

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1 Terms

3.1.1

subsample

sample obtained by means of a sample reduction procedure

3.1.2

test portion

sample used as a whole in a single test

3.1.3

lime

general term which includes quicklime, hydrated lime, lime slurry ("milk of lime"), defined and specified according to EN 459-1

3.1.4

lime content

amount of added lime in the soil, expressed as the percentage of lime mass to the dry mass of the soil, or expressed as the percentage to the sum of dry mass of the soil and added lime mass

UNI CEN/TS 17693-1:2022 5